

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (currently amended) A method for reducing a required signal-to-noise ratio in a time division multiple access (TDMA) link of a mobile network, the network including a first node and a second node, the method comprising:

receiving at the first node an initial TDMA signal burst from the second node;

determining initial link state variables of a link between the first and second nodes by interpreting a first preamble included in the initial TDMA signal burst, thereby synchronizing the first node to the initial TDMA signal burst; and

updating the initial link state variables utilizing a second preamble shorter than the first preamble included in a second ~~tracking the link state variables between the initial TDMA signal burst and subsequent receptions of TDMA signal burst~~[[s]] from the second node at the first node.

2. (cancelled)

3. (currently amended) The method of Claim ~~[[2]]~~ 1 wherein determining link state variables comprises utilizing the ~~[[long]]~~ first preamble to determine at least one of a ~~frequency offset from a nominal frequency~~, a carrier phase, a ~~signal amplitude~~, a symbol phase, and a word phase.

4. (currently amended) The method of Claim 1 wherein ~~tracking~~ updating the link state variables comprises:

storing the initial link state variables in a database of the first node; and

~~receiving at the first node at least one subsequent TDMA signal burst from the second node, the subsequent TDMA signal burst including a short preamble.~~

5. (currently amended) The method of Claim 4 wherein ~~tracking~~ updating the link state variables further comprises:

fetching the stored initial link state variables from the database;

utilizing the stored initial link state variables as a starting point; and

interpreting the second preamble to update the stored ~~updating the~~ link state variables ~~utilizing the short preamble~~, thereby synchronizing the first node to the ~~subsequent~~ second TDMA signal burst.

6. (currently amended) The method of Claim 5 wherein tracking the link state variables further comprises storing the updated link state variables in the database.

7. (currently amended) A system for providing a reduced signal-to-noise ratio requirement in time division multiple access (TDMA) links, within a mobile network, said system comprising:

a first node; and

a second node configured to transmit an initial TDMA signal burst to said first node, and wherein said first node configured to:

receive the initial TDMA signal burst;

determine initial link state variables of a link between the first and second nodes by interpreting a first preamble included in the initial TDMA signal burst, thereby synchronizing the first node to the initial TDMA signal burst; and

update the initial link state variables utilizing a second preamble shorter than the first preamble included in a second ~~track link state variables between the initial TDMA signal burst and at least one subsequent reception of a~~ TDMA signal burst transmitted from said second node to said first node.

8. (cancelled)

9. (currently amended) The system of Claim 7 wherein said link state variables comprise at least one of ~~a frequency offset from a nominal frequency~~, a carrier phase, ~~a signal amplitude~~, a symbol phase, and a word phase.

10. (currently amended) The system of Claim 7 wherein to track said link state variables, said first node is further configured to:

store said initial link state variables in a database of said first node; and

~~receive at said first node at least one subsequent TDMA signal burst from said second node, the subsequent TDMA signal burst including a short preamble.~~

11. (currently amended) The system of Claim 10 wherein to track said link state variables, said first node is further configured to:

retrieve said stored link state variables from said database;

utilize said stored initial link state variables as a starting point; and

interpret said second preamble to update said stored link state variables ~~utilizing the short preamble~~, thereby synchronizing said first node to ~~the subsequent~~ said second TDMA signal burst.

12. (currently amended) The system of Claim 11 wherein to track said link state variables, said first node is further configured to store said updated link state variables in said database.

13. (currently amended) A method for reducing a signal-to-noise ratio requirement in a time division multiple access (TDMA) link of a mobile network, the network including a first node and a second node, the method comprising:

receiving at the first node an initial TDMA signal burst from the second node, the initial TDMA signal burst including a [[long]] first preamble;

utilizing the [[long]] first preamble to determining link state variables;

storing the link state variables in a database of the first node;

receiving at the first node ~~at least one subsequent~~ a second TDMA signal burst from the second node, the ~~subsequent~~ second TDMA signal burst including a ~~short~~ second preamble that is shorter than the first preamble, the second preamble utilized in combination with the stored link state variable to determine updated link state variables; and

storing the updated ~~updating the stored~~ link state variables in the database of the first node upon reception of the ~~subsequent~~ second TDMA signal burst.

14. (currently amended) The method of Claim 13 wherein utilizing the ~~[[long]]~~ first preamble to determine link state variables comprises utilizing the ~~[[long]]~~ first preamble to determine at least one of ~~a frequency offset from a nominal frequency,~~ a carrier phase, ~~a signal amplitude,~~ a symbol phase, and a word phase.

15. (currently amended) The method of Claim 13 wherein updating the retained link state variables comprises:

retrieving the stored link state variables from the database; and

utilizing the stored link state variables as a starting point

interpreting the second preamble to update the stored ~~updating the~~ link state variables ~~utilizing the short preamble~~.

16. (cancelled)